

Fuel Line Cleaner (FLC)

Fuel Line Cleaner

Product properties

The product removes operationally caused contamination in the entire fuel system, from the tank to the combustion chambers. It removes resin and stickiness the carburettor and injection nozzle areas and removes further carbon residues and soot deposits within the entire upper cylinder area. Humidity and condensation is also eliminated in the complete fuel system and the product lubricates and protects the upper cylinder area.

Area of application

Suitable for all petrol powered engines. Motor vehicles, motorcycles and other high performance engines (e.g. ships and boats, Go-Karts, racing motors, lawn mowers, etc.)

Application

Add to the fuel system before filling up. Use during every service at intervals recommended by the manufacturer. For best results use the Clear Flow machine as instructed. We do not guarantee results if FLC is used with injection cleaning equipment other than ours. Not for retail. This product is for professional use only. Treats up to 80L petrol. Mixing ratio 1:200

Consumption

375 ml sufficient for up to 80 ltrs fuel. Mixing Ratio 1:200

Reaction time

Works while engine is running

Technical data

Physical state: liquid

Colour: red

Odour: aromatic

Initial boiling point and boiling range: 110 - 116 °C

Flashpoint: -6.5 °C

Lower explosion limit: 0,6 Vol.-%

Upper explosion limit: 12 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 20 hPa

Density at 68 °F: 0.78-0.82 g/cm³

Water resistant

Available sizes	Item no.	PU
375ml	P1101	28
1L	P1109	12
5L	P1102	4
10L	P1108	1
20L	P1107	1



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

02.10.2019